

TBK

TIEDKE - BÜHLING - KINNE & PARTNER (GbR)

DT15 Rec'd PCT/PTO 06 JAN 2005

10/520430

TBK-Patent, Bavariaring 4-6, 80336 München, Tel.: +49 89 544690, Fax: +49 89 532611 (G3) +49 89 5329095 (G3+G4), postoffice@tbk-patent.de

VIA FAX AND MAIL (including 11 pages in total)

TBK-Patent POB 20 19 18 80019 München

PRV InterPat

Box 5055

SE-102 42 Stockholm

Patentanwälte
Dipl.-Ing. Reinhard Kinne
Dipl.-Ing. Hans-Bernd Pellmann
Dipl.-Ing. Klaus Grams
Dipl.-Ing. Aurel Vollnhals
Dipl.-Ing. Thomas J.A. Leson
Dipl.-Ing. Dr. Georgi Chivarov
Dipl.-Ing. Matthias Grill
Dipl.-Ing. Alexander Kühn
Dipl.-Ing. Rainer Böckelen
Dipl.-Ing. Stefan Klingele
Dipl.-Chem. Stefan Bühling
Dipl.-Ing. Ronald Roth
Dipl.-Ing. Jürgen Faller
Dipl.-Ing. Hans-Ludwig Trösch
Rechtsanwälte
Michael Zöbisch

May 26, 2004

PCT-Patent Application No.: PCT/IB02/03030

NOKIA CORPORATION et al.

Our ref: WO 32586

(Frist: 13.06. Eing.)

Reference is made to the Written Opinion dated April 14, 2004.

Documents filed:

Enclosed herewith new claims 1 to 19 are filed. Claims 1 to 19 replace the original claims 1 to 20. In order to elucidate the individual amendments effected, a corresponding claim amendment sheet is also enclosed herewith.

Disclosure of amendment:

Claims 1 to 19 as filed herewith are substantially based on the original claims 1 to 20, as set out herein in greater detail. Claim 1 as filed herewith corresponds to a combination of original claims 1 and 4, claims 2 and 3 correspond to original claims 2 and 3, and claims 4 to 16 correspond to original claims 5 to 17, respectively, with the numbering being now accordingly adapted. Claim 17 corresponds to original claim 18, now being adapted to the valid version of claim 1. Claims 18 and 19 correspond to

Dresdner Bank, München
Deutsche Bank, München
Postbank, München
Mizuho Corp. Bank, Düsseldorf
UFJ Bank Limited, Düsseldorf
Steuernr.: 9 148/641/28007 Ust-ID/VAT: DE 1307 480 35

Kto. 3939 844
Kto. 2861 060
Kto. 6704 3804
Kto. 810 423 3007
Kto. 500 047

BLZ 700 800 00
BLZ 700 700 24
BLZ 700 100 80
BLZ 300 207 00
BLZ 301 307 00

IBAN-Nr.: DE47 7008 0000 0393 9844 00
IBAN-Nr.: DE14 7007 0024 0286 1060 00
IBAN-Nr.: DE04 7001 0080 0067 0438 04
IBAN-Nr.: DE75 3002 0700 8104 2330 07
IBAN-Nr.: DE09 3013 0700 0000 5000 47

BIC: DRES DE FF 700
BIC: DEUT DE DB MUC
BIC: PBNK DE FF
BIC: MHCB DE DD
BIC: SANW DE DX

FA216

original claims 19 and 20, respectively, with the numbering being accordingly adapted.

Apart from the original disclosure of the amendment in original claim 4, this amendment is held to be disclosed, for example and among others, on page 15, lines 4 to 7 of the original specification.

Novelty and inventive step:

With the above-referenced Written Opinion, the subject-matter of original claim 4 was not objected to for lack of inventive step.

Hence, the subject-matter as presently claimed in the independent claims 1 and 17, respectively is strongly held to be neither anticipated by the cited prior art nor to be rendered obvious thereby.

Therefore, a positive International Preliminary Report on Patentability under chapter II of the PCT is respectfully awaited.

Jürgen Faller
Patentanwalt
TBK-Patent

Enclosures:

- Claims 1 to 19
- Claim amendment sheet for claims 1 to 19

Enclosure of May 26, 2004

PCT-Patent Application No.: PCT/IB02/03030

Nokia Corporation et al.

Our ref.: WO 32586

5

CLAIMS

- 10 1. A method of carrying an application level message
encapsulated inside a signaling message of an access
network, said method comprising the steps of:
- 15 receiving (1) an application level message from a
sender application process to an access network signaling
process;
- adapting (3) said application level message and
encapsulating it in a signaling message of an access
network; and
- 20 delivering (1, 3, 4) said encapsulated application
level message to a receiver application process by
transmitting said signaling message, wherein said
encapsulated application level message is transparent to
the means of said access network transmitting said
signaling message, and
- 25 wherein said application level message includes an
indication under which conditions the signaling message
should be delivered.
- 30 2. A method according to claim 1, wherein said sender
application process is performed in a mobile terminal being
attached to said access network.
- 35 3. A method according to claim 1, wherein said sender
application process is performed in a server providing a
corresponding application.

4. A method according to claim 1, wherein said indication comprises an address of the application receiver process being one of the group comprising a logical name, an IP address, and a port number.

5

5. A method according to claim 1 or 4, wherein said indication comprises another indication whether said signaling message should be delivered even if the Quality-of-Service changes.

10

6. A method according to claim 1, wherein said method is implemented in a call establishment procedure for Voice over the Internet Protocol (VoIP).

15

7. A method according to claim 1, wherein said encapsulated application level message is included in an activation request within a Packet Data Protocol (PDP) context signaling.

20

8. A method according to claim 3, wherein said application server is one of the group of proxy call state control function means (P-CSCF), push proxy server means, and instant message server means.

25

9. A method according to claim 7, wherein said packet data protocol (PDP) context signaling is embedded into one of the group of a Session Initiation Protocol (SIP) signaling, a Resource Reservation Protocol (RSVP) signaling, and a Point to Point Protocol (PPP) signaling.

30

10. A method according to claim 7, wherein said encapsulated application level message includes a complete Session Initiation Protocol (SIP) message.

11. A method according to claim 10, wherein a Gateway GPRS Support Node (GGSN) creates a Internet Protocol/User Datagram Protocol header and forwards said complete Session Initiation Protocol (SIP) message to a Session Initiation Protocol (SIP) proxy means.

12. A method according to claim 11, wherein said header is created by using information sent in an optional application level message information element.

13. A method according to claim 11, wherein said header is created by using information coming from said Packet Data Protocol (PDP) context signaling.

14. A method according to claim 11, wherein said header is created by using information coming from a configuration process.

15. A method according to claim 7, wherein

said encapsulated application level message indicates that a Gateway GPRS Support Node (GGSN) shall send a context response message only when a response of said receiver application process is received, as a reaction to which said Gateway GPRS Support Node (GGSN) starts a timer to wait for answer; and wherein

a reply before the expiry of said timer is copied as a new encapsulated application level message in said context response message, and in case of no reply before the expiry of said timer an indication that said receiver application process does not answer is copied as a new encapsulated application level message in said context response message.

16. A method according to claim 7, wherein

said encapsulated application level message indicates that a Gateway GPRS Support Node (GGSN) shall send a

context response message immediately, as a reaction to which said Gateway GPRS Support Node (GGSN) sends a context response message immediately, whereas a response of said receiver application process is returned to said sender application process in a non-encapsulated manner as normal traffic.

17. A system adapted to perform a transmission of an application level message encapsulated inside a signaling message of an access network, comprising:

receiving means adapted to receive an application level message from a sender application process to an access network signaling process;

adapting means for encapsulating said application level message in a signaling message of an access network; and

delivering means adapted to deliver said encapsulated application level message to a receiver application processing means, and

wherein said application level message includes an indication under which conditions the signaling message should be delivered.

18. A system according to claim 17, further comprising a server adapted to perform said sender application process.

19. A system according to claim 18, wherein said server is one of the group of proxy call state control function means (P-CSCF), push proxy server means, and instant message server means.